

Main Specifications		Conical Twin Screw Extruder							Vacuum Sizing Tank			Spray Bath			Haul - off		Cutting Saw	
Machine Model	Min. Pipe OD (mm)	Max. Pipe OD (mm)	Max. Plasticizing Capacity (kg./hr.)	Max. Output (kg./hr.)	Main Drive (kw)	Heating Barrels (kw)	Heating Die (kw)	Screw Speed Variation (RPM)	Pump Drive (kw)	Length (mtrs.)	Water Requirements Circulating (liters/min)	Length (mtrs.)	Water Requirement Circulating (liters/min)	Drive Range (kw)	No. of Arms	Width of Belt (inch.)	Saw Dia (mm)	Saw Drive Load (kw)
HPMC 45/90	16	50	90	80	15	11	3	1-37	2.25	3.0	400	3	-	1.5	2	4	300	0.75
HPMC 51/105	16	200	170	150	16.5	15	5	1-37	2.25	1.0	400	5	-	4	2	6	500	1.5
HPMC 65/132	63	225	300	250	37	20	8	1-37	-	-	-	6	450	4	2	6	500	1.5
HPMC 80/156	110	315	425	350	55	35	12	1-37	-	-	-	6	500	5.5	3	2.5	200	2.25
HPMC 92/188	315	630	600	450	75	45	20	1-37	-	-	-	6+6	1000	7.5	6	2.5	200	2.25